

Termostati bojlera

Kapilarni termostat

10.10.015

KT-165 AOJ



Tmax = 65 °C
Dužina osovine: 23 mm
Dužina kapilare: 650 mm
16 (4) A, 250 V ~
Metalflex, Slovenija

Kapilarni termostat

10.10.016

KT-165 AOA



Tmax = 75 °C
Dužina osovine: 23 mm
Dužina kapilare: 650 mm
16 (4) A, 250 V ~
Metalflex, Slovenija

Kapilarni termostat

10.10.023

KT-165 77/15



Tmax = 77 °C
Dužina osovine: 15 mm
Dužina kapilare: 650 mm
16 (4) A, 250 V ~
Metalflex, Slovenija

Kapilarni termostat

10.10.024

KT-165 85/23



Tmax = 85 °C
Dužina osovine: 23 mm
Dužina kapilare: 650 mm
16 (4) A, 250 V ~
Metalflex, Slovenija

Kapilarni termostat

10.10.027

KT-165 90/15



Tmax = 90 °C
Dužina osovine: 15 mm
Dužina kapilare: 650 mm
16 (4) A, 250 V ~
Metalflex, Slovenija

Kapilarni termostat

10.10.028

NT-112 EM / 2



Tmax = 77 °C
Dužina osovine: 15 mm
Dužina kapilare: 650 mm
16 A, 400 V ~
Tecasa, Španija

Kapilarni termostat

10.10.029

NT-112 EM / 1



Tmax = 85 °C
Dužina osovine: 23 mm
Dužina kapilare: 650 mm
16 A, 400 V ~
Tecasa, Španija

Kapilarni termostat

10.10.031

NT-112 EM/4



Tmax = 85 °C
Dužina osovine: 15 mm
Dužina kapilare: 650 mm
16 A, 400 V ~
Tecasa, Španija

Kapilarni termostat

10.10.251

KT-165 BTA



3 kontakta
Tmax = 85 °C
Dužina osovine: 23 mm
Dužina kapilare: 1350 mm
16 A, 250 V ~
Metalflex, Slovenija

Kapilarni termostat, sigurnosni

10.10.032

KV-441 D



Tiz = 115 - 10 °C
Sa pločicom za montažu
Dužina kapilare: 600 mm
16 A, 250 V ~
Metalflex, Slovenija

Štapni termostat sa polugom

10.10.043

TRS 77 - ubodni



Tmax = 65°C
Tiz = 75°C
Dužina sonde: 275 mm
20 A, 250 V ~
V.E.B.E. Italija

Štapni termostat

10.10.045

TRS 77 - ubodni



Tmax = 65°C
Tiz = 75°C
Dužina sonde: 275 mm
20 A, 250 V ~
V.E.B.E. Italija

Štapni termostat

10.10.046

Thermowatt R-T-S 3



Tmax = 65°C
Tiz = 75°C
Dužina sonde: 280 mm
16 A, 250 V ~
Thermowatt, Italija

Štapni termostat

10.10.047

Thermowatt T-E-S



Tmax = 75°C
Tiz = 84°C
Dužina sonde: 280 mm
20 A, 220 V ~
Thermowatt, Italija

Štapni termostat

10.10.048

Thermowatt R-T-M



Tmax = 73°C

Dužina sonde: 275 mm
15A, 250 V ~
Thermowatt, Italija

Štapni termostat

10.10.049

DT 127



Tmax = 75°C
Tiz = 85°C
Dužina sonde: 280 mm
16A, 220 V ~
Metalflex, Slovenija

Kapilarni termostat

10.10.060

711.11338.00A

3 kontakta

Tmax = 90°C

Dužina osovine: 14 mm

Dužina kapilare: 1500mm

16 A, 250 V ~

T&G, Italija



Kapilarni termostat

10.10.061

711.71338.00A

3 kontakta

Tmax = 120°C

Dužina osovine: 14 mm

Dužina kapilare: 1500mm

16A, 250 V ~

T&G, Italija



Kapilarni termostat

10.10.200

711.G1339.00A

3 kontakta

Tmax = 210°C

Dužina osovine: 14 mm

Dužina kapilare: 1500mm

16 A, 250 V ~

T&G, Italija



Kapilarni termostat

10.10.440

712.10228.00A

Tmax = 90°C

Regulacija na šraf

Dužina kapilare: 1000mm

16 A, 250 V ~

T&G, Italija



Kapilarni termostat

10.10.442

712.10328.00A

3 kontakta Tmax

= 90°C

Regulacija na šraf

Dužina kapilare: 1000mm

16 A, 250 V ~

T&G, Italija



Kapilarni termostat, sigurnosni

10.10.444

961.90328.00A

Opseg = 70 ÷ 90°C

Manualno podešavanje

Dužina kapilare: 1000mm

16 A, 250 V ~

T&G, Italija



Termički osigurač

10.10.976

TV 433 L1

Tiz = 117°C

Dužina provodnika:

355 mm

16 A, 220 V ~

Metalflex, Slovenija



Termički osigurač

10.10.975

TV 433 L7

Tiz = 117°C

Dužina provodnika:

L1=355 mm, L2=910mm

16 A, 220 V ~

Metalflex, Slovenija

